

UDYZ Quickview

Transition Level / Altitude	FL130/11500ft
Stations	UDYZ_GND: 119.0 UDYZ_TWR: 128.0 UDYZ_APP: 126.0 UDDD_CTR: 1127.6 UDDD_FIS: 1129.7
VOICE-ATIS available	YES . XT-Division highly recommend to use VOICE-ATIS wherever available

Departures	
Initial climb clearance	7000ft
Squawk Code	Use SSR feature of AURORA or 1000
Handoff TWR to higher Station	When airborne
Handoff APP/DEP to higher Station	Clear aircraft to FL140, handoff not later than FL120.

Arrivals	
Descent clearance from CTR and handoff	Descent FL150 handoff to APP not later than FL170.
STARs vs VECTORS	XT-Division highly recommend to use STARs and to use shortcut directs on STARs, however VECTOR service available on Pilots request. ATC must ensure MRVA limitations.
Handoff to TWR	Handoff to TWR when Pilot reports established on approach given by ATC.

Gates and Parking Stands	
International	10 – 14 and 15 - 22
Domestic	5 - 8 and 15 – 22
Cargo	23 - 26
General Aviation	15 - 22
VIP and Government	0 and 15 - 22

Special Notes	
Notams	Respect real life NOTAMS if possible (eg. Runway closures)
Runway	Runway 27 for takeoff and runway 09 for landing recommended up to 10kts tailwind.